

Fixed Glazing System SV1051

The STOBAG profile system SV1051 offers a range of set-ups in the area of non-insulated glazing. This is suitable for use with several of our products, with roof inclines of 2° – 25°.

Type: SV1051/1 Glass piece

Type: SV1051/2 Fixed glass panel with roof pitch

Type: SV1051/3 Fixed glass panel

Type: SV1051/4 Al piece

Pivot-hung windows can be installed in the single types as an option.

The STOBAG SV1051 profile system is manufactured under licence by aliplast Aluminium Systems.

Profile system

- Non-thermally insulated/uninsulated aluminium profiles
- Installation depth 51 mm

Opening options / Fittings

Fixed glazing with pivot-hung windows can be individually extended as an option.

Tilt windows:

1-leaf tilt windows are optionally available.

- Opening to inside
- Leaf widths 400 to 1300 mm
- Leaf heights 410 to 1600 mm
- Installation in type SV1051/1, SV1051/2 and SV1051/3 possible
- Standard fittings anodised colourless comprising:
 - Tilt fittings
 - Skylight catch

Impermeability and Ventilation

- Rain and wind impermeability is guaranteed by EPDM seals

Glazing

- Standard glass laminated safety glass (USG) 8-2 with clear or matt foil
- Panes can be easily changed at a later date

Planning / Orders

- Planning and orders are material-related and may vary