

## **FIXED GLAZING SYSTEM SV1051**

The STOBAG profile system SV1051 offers a range of set-ups in the area of non-insulated glazing. This is suitable for use with several of our products, with roof inclines of 2° – 25°.

<b>Type: SV1051/1</b>	<b>Glass piece</b>
<b>Type: SV1051/2</b>	<b>Fixed glass panel with roof pitch</b>
<b>Type: SV1051/3</b>	<b>Fixed glass panel</b>
<b>Type: SV1051/4</b>	<b>Al piece</b>

Pivot-hung windows can be installed in the single types as an option.

The STOBAG SV1051 profile system is manufactured under licence by aliplast Aluminium Systems.

### **Profile system**

- Non-thermally insulated/uninsulated aluminium profiles
- Installation depth 51 mm

### **Opening options / Fittings**

Fixed glazing with pivot-hung windows can be individually extended as an option.

### **Tilt windows**

1-leaf tilt windows are optionally available.

- Opening to inside
- Leaf widths 400 to 1300 mm
- Leaf heights 410 to 1600 mm
- Installation in type SV1051/1, SV1051/2 and SV1051/3 possible
- Standard fittings anodised colourless comprising:

Tilt fittings

Skylight catch

### **Impermeability and Ventilation**

- Rain and wind impermeability is guaranteed by EPDM seals

### **Glazing**

- Standard glass laminated safety glass (USG) 8-2 with clear or matt foil
- Panes can be easily changed at a later date

### **Planning / Orders**

- Planning and orders are material-related and may vary