

SIGMA S7200

Folding arm awning with operating handle. Fabric cover. Retraction and extension with detachable operating handle. Bevel gearbox with gearbox reduction 4,5:1. Awning without mounting bar. Combined brackets for wall fixing, arm fixation and support for roller tube. Folding arms made of extruded aluminium profiles, with precision joints made of aluminium casting. Integrated tension springs and stainless steel cables and cable protection sleeves over the middle joint. Roller tube made of galvanised steel with groove for the cover fixation. Combined brackets with security against knock-ups and adjustable fall. Front rail made of extruded multiple chamber aluminium profile with end caps, grooves for the cover and the valance, with fixation groove for the folding arms. Operating handle powder coated matching the standard colours, with hook and plastic handle.

Options:**Electric drive**

With an electronic limit switch: Tubular AC motor 230 V, 50 Hz or 120 V, 60 Hz (according to the country) with electromechanical brakes and electronic end stop. Thermal protection, protection class IP44 (spray water), with 50 – 150 cm connection cable.

Remote control motor with an electronic limit switch: Tubular AC motor 230 V, 50 Hz or 120 V, 60 Hz (according to the country) with electromechanical brakes and electronic end stop. Integrated radio receiver, thermal protection, protection class IP44 (spray water), with 50 – 150 cm connection cable.

Top board

The top board made of extruded aluminium profiles is fixed with a wall yoke and protects the awning against environmental influences.